

# IN DOOR

Model	CTACG0326N	CTACG0526N	CTACG0826N	CTACG1026N
Overall dimension (flange)	500*300*168mm	508*300*216mm	550*280*280mm	950*400*241mm
Weight	20Kg	23Kg	23Kg	36Kg
Cooling capacity (L35/L35)	300W	500W	800W	1060W
Power consumption (L35/L35)	140W	280W	400W	420W
Operating temperature range	20°C~55°C	20°C~55°C	20°C~55°C	20°C~55°C
Noise	60dB(A)	60dB(A)	60dB(A)	65dB(A)
Max nominal current	1.4A	2.5A	3.5A	3.5A
Starting current	5A	5A	5.4A	5.4A
Refrigerant	R134a	R134a	R134a	R134a
Air volume	180m <sup>3</sup> /h	180m <sup>3</sup> /h	210m <sup>3</sup> /h	310m <sup>3</sup> /h
Power supply	AC 230V±10% 50/60Hz	AC 230V±10% 50/60Hz	AC 230V±10% 50/60Hz	AC 230V±10% 50/60Hz
IP code	IP54	IP54	IP54	IP54
Finish	Outdoor powder RAL7035	Outdoor powder RAL7035	Outdoor powder RAL7035	Outdoor powder RAL7035

# IN DOOR

Model	CTACG1526N	CTACG2026N	CTACG2526N	CTACG3026N	CTACG4026N
Overall dimension (flange)	950*400*260mm	1580*400*295mm	1580*400*295mm	1580*400*295mm	1580*500*340mm
Weight	40Kg	45Kg	50Kg	52Kg	60Kg
Cooling capacity (L35/L35)	1560W	2000W	2700W	3000W	4000W
Power consumption (L35/L35)	636W	800W	1018W	1050W	1650W
Max Nominal current	5.9A	8.6A	10.8A	11A	17A
Starting current	11.7A	20.1A	20.1A	20.1A	36A
Operating temperature range	20°C~55°C	20°C~55°C	20°C~55°C	20°C~55°C	20°C~55°C
Noise	65db(A)	65db(A)	65db(A)	68db(A)	68db(A)
Refrigerant	R134a	R134a	R134a	R134a	R134a
Air volume	310m <sup>3</sup> /h	420m <sup>3</sup> /h	420m <sup>3</sup> /h	500m <sup>3</sup> /h	520m <sup>3</sup> /h
Power supply	AC 230V±10% 50/60Hz	AC 230V±10% 50/60Hz	AC 230V±10% 50/60Hz	AC 230V±10% 50/60Hz	AC 230V±10% 50/60Hz
IP code	IP54	IP54	IP54	IP54	IP54
Finish	Outdoor powder RAL7035	Outdoor powder RAL7035	Outdoor powder RAL7035	Outdoor powder RAL7035	Outdoor powder RAL7035

# OUT DOOR

Model	CTACD0626W	CTACD0826W	CTACD1026W	CTACD1526W	CTACD2026W
Overall dimension (flange)	582*352*175mm	784*483*175mm	784*483*175mm	784*482*210mm	784*482*210mm
Weight	23Kg	28Kg	28Kg	31Kg	32Kg
Cooling capacity (L35/L35)	600W	800W	1000W	1500W	2000W
Power consumption (L35/L35)	280W	360W	410W	650W	750W
Operating temperature range	-40~55°C	-40~55°C	-40~55°C	-40~55°C	-40~55°C
Noise	60dB(A)	65dB(A)	65dB(A)	65dB(A)	65dB(A)
Max nominal current	2.5A	3.5A	3.5A	4.5A	5A
Starting current	5A	5.4A	5.4A	10.7A	15.6A
Refrigerant	R134a	R134a	R134a	R134a	R134a
Air volume	180m <sup>3</sup> /h	366m <sup>3</sup> /h	366m <sup>3</sup> /h	366m <sup>3</sup> /h	500m <sup>3</sup> /h
Power supply	AC 230V±10% 50/60Hz	AC 230V±10% 50/60Hz	AC 230V±10% 50/60Hz	AC 230V±10% 50/60Hz	AC 230V±10% 50/60Hz
IP code	IP56	IP56	IP56	IP56	IP56
Finish	Outdoor powder RAL7035	Outdoor powder RAL7035	Outdoor powder RAL7035	Outdoor powder RAL7035	Outdoor powder RAL7035

# OUT DOOR

Model	CTACD2526W	CTACD3026W	CTACD4026W	CTACD5025W	CTACD7525W
Overall dimension (flange)	1190*521*225mm	1190*521*225mm	1350*550*300mm	1350*650*300mm	1660*711*350mm
Weight	60Kg	60Kg	70Kg	70Kg	85Kg
Cooling capacity (L35/L35)	2500W	3000W	4000W	5000W	7500W
Power consumption (L35/L35)	850W	1050W	1300W	1600W	2500W
Operating temperature range	-40~55°C	-40~55°C	-40~55°C	-40~55°C	-40~55°C
Noise	65dB(A)	70dB(A)	70dB(A)	70dB(A)	75dB(A)
Max nominal current	6A	7.5A	9.2A	11A	17.5A
Starting current	20.1A	20.1A	36A	36A	72A
Refrigerant	R134a	R134a	R134a	R407c	R407c
Air volume	550m <sup>3</sup> /h	600m <sup>3</sup> /h	600m <sup>3</sup> /h	700m <sup>3</sup> /h	1100m <sup>3</sup> /h
Power supply	AC 230V±10% 50/60Hz	AC 230V±10% 50/60Hz	AC 230V+10% 50/60Hz	AC 230V+10% 50/60Hz	AC 230V+10% 50/60Hz
IP code	IP56	IP56	IP56	IP56	IP56
Finish	Outdoor powder RAL7035	Outdoor powder RAL7035	Outdoor powder RAL7035	Outdoor powder RAL7035	Outdoor powder RAL7035